

MILAN S.r.l. a socio unico

**Head Office – Export department:**  
 Viale Europa, 74  
 20090 Cusago (MI) Italy  
 T. +39 02 9039.4556-4158  
 F. +39 02 9039.4551  
 www.taskercables.com

**Ufficio Commerciale e Centro Distribuzione**  
 Viale Europa 72 Strada F12  
 20090 Cusago (MI) Italy  
 T. +39 02 9039.0037-0059  
 F. +39 02 9039.0049  
 www.tasker.it

## Technical Datasheet

# tasker® C129 – 1x0,35 mm<sup>2</sup> Unbalanced Microphone Cable



**CATEGORY** Microphone Cable (See Audio Catalogue)  
**APPLICATIONS** Unbalanced Microphones and Sound Reproduction.

- A:** Black Soft **PVC** Sheath.  
Outer Diam. Ø 5,20 (±0,10) mm.
- B:** O.F.C. tinned copper braid shielding, covering 90%.
- C:** Core Insulation in transparent Compact PE.  
Diam. Ø 3,00 (±0,10) mm.
- D:** O.F.C. tinned copper formation 11x0,20 mm.  
Nom. Cross section 1x0,35 mm<sup>2</sup>.

**MARKING** **tasker®** C129 1x0,35 O.F.C.PROFESSIONAL NOISELESS Microphone  
Cable Low capacity

**CUSTOM PRODUCTION** This product may be custom produced also in **L.S.Z.H.** polymer, **PE, PUR**, with or without Metallic Armor.

### Cable Properties

<b>Conductor Resistance</b>	58,00 Ω/Km
<b>Capacity Core/Shield</b>	89 pF/m.
<b>Max Rated Voltage</b>	49 V
<b>Operative Temperature</b>	-15/+70°C

<b>USE</b>	<b>X</b>	Indoor	Interno Edificio	<b>INSTALLATION</b>	<b>X</b>	Fixed	Fissa	<b>INFORMATION</b>	<b>X</b>	RoHS2 Compliant
<b>Impiego</b>		Outdoor Limited	Esterno Limitato	<b>Posa</b>	<b>X</b>	Restricted Mobile	Mobile Limitata	<b>Informazioni</b>	<b>X</b>	Ver. A / 26.05.17
		Outdoor	Esterno			Mobile	Mobile			
		Outdoor Direct Burial	Esterno Interrato			Mobile in Drag Chain	Mobile in Catena			10% measurement tolerance, unless otherwise indicated