

## S-VHS Video cable



**Applications:**  
Flexible cable with separately shielded and insulated cores for assembled cables. Suitable to connect Mini-DIN 4 poles S-VHS plug.

**Characteristics:**  
 Conductors: O.F.C. tinned copper  
 Cond. Insulation: PVC  
 Core colours: Yellow, Grey  
 Shields: Spiral covering 100% O.F.C. tinned copper  
 PVC  
 Inner Sheaths: PVC  
 Inner Sheath colours: White, Red  
 External Sheath: PVC  
 Sheath colour: Black



| tasker® Code | Cond. number | Nominal section mm <sup>2</sup> | Cond. Format. mm. | External Core Ø mm. | External Inner Sheath Ø mm. | External Cable Diameter mm. | Reel or Spool (* pag. II) |      |     |
|--------------|--------------|---------------------------------|-------------------|---------------------|-----------------------------|-----------------------------|---------------------------|------|-----|
|              |              |                                 |                   |                     |                             |                             | mt.                       | Type | Kg. |
| C200         | 2            | 2 x 0,08 (28 AWG)               | 12x0,10           | 1,0                 | 2,0                         | 4,6                         | 100                       | B    | 3,0 |

*nightly blue®*



| Conductor Resistance | Capacity Core/core       | Capacity Core/shield     |
|----------------------|--------------------------|--------------------------|
| Ω/Km ± 5%            | pF/mt                    | pF/mt                    |
| 210                  | 65                       | 230                      |
|                      | Max rated Voltage AC - V | Operative Temperature °C |
|                      | 49                       | -15 / +70                |

## S-VHS Video & Audio cable



**Applications:**  
Special flat cable with separately shielded and insulated cores for assembled cables. Flat cable composed of: 1 S-VHS and 2 Audio cables. Suitable to connect n° 1 Mini-DIN 4 poles S-VHS plug and n° 2 RCA audio plugs.

**Characteristics:**  
**S-VHS**  
 Conductors: O.F.C. tinned copper  
 Cond. Insulation: PVC  
 Core colours: Yellow, Grey  
 Shields: Spiral covering 100% O.F.C. tinned copper  
 PVC  
 Inner Sheaths: PVC  
 Inner Sheath colours: White, Red  
**Audio**  
 Conductors: O.F.C. red copper  
 Cond. Insulation: Compact PE  
 Core colours: Red, White  
 Shields: Spiral covering 100% O.F.C. red copper  
 PVC  
 External Sheath: PVC  
 Sheath colour: Blue-night

| tasker® Code | Cond. number | Nominal section mm <sup>2</sup>         | Cond. Format. mm. | External Core Ø mm. | External Inner Sheath Ø mm. | External Cable Dimension mm. | Reel or Spool (* pag. II) |      |     |
|--------------|--------------|-----------------------------------------|-------------------|---------------------|-----------------------------|------------------------------|---------------------------|------|-----|
|              |              |                                         |                   |                     |                             |                              | mt.                       | Type | Kg. |
| C142         | 2<br>+2      | 2 x 0,08 (28 AWG)<br>+2 x 0,25 (23 AWG) | 12x0,10<br>8x0,20 | 1,0<br>2,3          | 2,0                         | 5,0 x 14,5                   | 100                       | B    | 9,5 |



| Conductor Resistance | Capacity Core/core       | Capacity Core/shield     |
|----------------------|--------------------------|--------------------------|
| Ω/Km ± 5%            | pF/mt                    | pF/mt                    |
| 210                  | 65                       | 230                      |
| 75                   | 36                       | 96                       |
|                      | Max rated Voltage AC - V | Operative Temperature °C |
|                      | 49                       | -15 / +70                |