

## Microphone cables



**Applications:** Unbalanced microphone cable and for sound reproduction.

**Characteristics:**  
 Conductor: O.F.C. tinned copper  
 Cond. Insulation: Compact PE  
 Core colour: Transparent  
 Shield: Braided covering 90%  
 O.F.C. tinned copper  
 Sheath: PVC  
 Sheath colour: Black



tasker® Code	Cond. number	Nominal section mm <sup>2</sup>	Cond. Format. mm.	External Core Ø mm.	External Cable Diameter mm.	Reel or Spool (* pag. II)		
						mt.	Type	Kg.
C129	1	1 x 0,35 (22 AWG)	11x0,20	3,0	5,2	100	B	3,5

*nightly blue®*



**Applications:** Unbalanced microphone cable and for sound reproduction.

**Characteristics:**  
 Conductor: O.F.C. tinned copper  
 Cond. Insulation: Compact PE  
 Core colour: Transparent  
 Shield: Braided covering 100%  
 O.F.C. tinned copper  
 Sheath: PVC  
 Sheath colour: Transparent



tasker® Code	Cond. number	Nominal section mm <sup>2</sup>	Cond. Format. mm.	External Core Ø mm.	External Cable Diameter mm.	Reel or Spool (* pag. II)		
						mt.	Type	Kg.
C195	1	1 x 0,50 (20 AWG)	16x0,20	2,1	6,0	100	B	4,2

*nightly blue®*



**Applications:** Professional unbalanced microphone cable and for sound reproduction.

**Characteristics:**  
 Conductor: O.F.C. red copper  
 Cond. Insulation: PVC  
 Core colour: White  
 Inner cotton: Braided covering 95%  
 Shield: Braided covering 95%  
 O.F.C. tinned copper  
 Sheath: PVC  
 Sheath colours: Red, Blue, Yellow, Green



tasker® Code	Cond. number	Nominal section mm <sup>2</sup>	Cond. Format. mm.	External Core Ø mm.	External Cable Diameter mm.	Reel or Spool (* pag. II)		
						mt.	Type	Kg.
C209	1	1 x 0,75 (18 AWG)	24x0,20	3,0	6,2	100	B	5,3

Conductor Resistance Ω/Km ± 5%	Capacity Core/core pF/mt	Capacity Core/shield pF/mt
60		89
	Max rated Voltage AC - V 49	Operative Temperature °C -15 / +70

Conductor Resistance Ω/Km ± 5%	Capacity Core/core pF/mt	Capacity Core/shield pF/mt
45		130
	Max rated Voltage AC - V 49	Operative Temperature °C -15 / +70

Conductor Resistance Ω/Km ± 5%	Capacity Core/core pF/mt	Capacity Core/shield pF/mt
30		236
	Max rated Voltage AC - V 49	Operative Temperature °C -15 / +70