

Product datasheet DECOSTAR 51S 20 W 12 V 36° GU5.3

DECOSTAR 51S Standard | Halogen dichroic reflector lamps with 51 mm diameter

- General illumination Entrance lighting Workplace lighting Kitchen lighting Mirror lighting Object lighting



 Brilliant accent light Dichroic reflector reduces the heat in the light beam by up to 66 % Approved for use in open luminaires (to IEC 60598-1) UV filter Contains no mercury



Technical data

Electrical data

Nominal wattage	20.00 W
Nominal voltage	12 V
Rated wattage	20.00 W


Photometrical data

Nominal useful luminous flux 90°	210 lm
Luminous intensity	480 cd
Light color (designation)	Warm White
Rated color temperature	2800 K
Color rendering index Ra	100
Lumen main.fact.at end of nom.life time	0.75
Rated useful luminous flux 90°	210 lm
Rated peak intensity	480 cd
Color temperature	2800 K
Luminous flux	210 lm

Light technical data

Beam angle	36 °
Nominal beam angle	36 °
Starting time	0.0 s
Rated beam angle (half peak value)	36.00 °

Dimensions & weight



Diameter	51.0 mm
Overall length	46.0 mm
Outer bulb	Т9

Product weight	32.24 g
Length	46.0 mm
Maximum diameter	51.0 mm

Lifespan

Rated lamp life time	4000 h
Number of switching cycles	100000

Additional product data

Base (standard designation)	GU5.3
Mercury content	0.0 mg
Mercury-free	Yes

Capabilities

Burning position	Any
Dimmable	Yes

Certificates & standards

Energy efficiency class	G
Energy consumption	22 kWh/1000h


Country specific categorizations

ILCOS	HRGS//UB-20-12-GU5.3-51/36
Order reference	44860 WFL 20W 1

Environmental information

Date of Declaration10-11-2021		
Primary Article Identifier	4050300272511	
Candidate List Substance 1	No declarable substances contained	
CAS No. of substance 1	No CAS	
Declaration No. in SCIP database	No declarable substances contained	

Light Distribution



HAL_DICRO_AK

Logistical Data

Product code	Product description	Packaging unit (Pieces/Unit)	Dimensions (length x width x height)	Volume	Gross weight
4050300272511	DECOSTAR 51S 20 W 12 V 36° GU5.3	Shipping carton box 20 Pieces Folding carton box	202 mm x 124 mm x 147 mm	3.68 dm³	856.00 g
4050300272511	DECOSTAR 51S 20 W 12 V 36° GU5.3	Shipping carton box 60 Pieces Folding carton box	290 mm x 135 mm x 245 mm	9.59 dm ³	2578.00 g

The mentioned product code describes the smallest quantity unit which can be ordered. One shipping unit can contain one or more single products. When placing an order, for the quantity please enter single or multiples of a shipping unit.

References / Links

For light distribution curves see

www.osram.com

Disclaimer

Subject to change without notice. Errors and omission excepted. Always make sure to use the most recent release.

OSRAM is distribution partner of LEDVANCE of LAMPS



OSRAM GmbH Marcel-Breuer-Strasse 6 80807 Munich, Germany