


FOR 客户名称	APPROVED 客户确认签字	ATTN 销售负责人

Part Number:AD16-22■/△/▲

■	Design code	△	Lamp Color	▲	Lamp Voltage
M	Buzzer	R	Red	12V	AC/DC 12V
JM	Intermittent buzzer	G	Green	24V	AC/DC 24V
S	Filcker	Y	Yellow	36V	AC/DC 36V
SM	Filcker buzzer	B	Blue	48V	AC/DC 48V
SSM	Duble Filcker buzzer	W	White	110V	AC 110V
				220V	AC 220V
				380V	AC 380V
Other voltage can be made to order					

PANEL CUTOUT  
MAX.PANEL THICKNESS  
6 mm



**SPECIFICATIONS:**

- 1.Electrical Life: ≥40,000 hours.
- 2.Permitted Voltage ±20%(≥110V).
- 3.Dielectric Strength: 2.5KV(AC RMS),1min.
- 4.Usage Frequency(AC): 50~60 Hz.
- 5.Rated Operating Current: ≤20mA.
- 6.Brightness: ≥100cd/m².
- 7.Comparative Tracking Index CT1≥100,flame retardant.
- 8.Insulation Resistance: Ui≤60V,5MΩ,60V<Ui≤660V,50MΩ.
- 9.IP Class: IP40.
- 10.Sound intensity: ≥80db (10cm) .

**MATERIALS:**

- 1.Head: PC.
- 2.Body: PA.
- 3.Base: PA.

BRAND 品牌 <b>ONPOW</b>	<b>红波按钮制造有限公司</b> ONPOW PUSH BUTTON MANUFACTURE CO.,LTD.			
	USED 用途		APPD 审核 CH 2020/04/10	
THESE DRAWINGS AND SPECIFICATIONS ARE THE PROPERTY OF ONPOW PUSH BUTTON MANUFACTURE CO.,LTD. AND SHALL NOT BE REPRODUCED COPIED OR USED IN ANY MANNER WITHOUT THE PRIOR WRITTEN CONSENT OF ONPOW PUSH BUTTON MANUFACTURE CO.,LTD.		FINISH 处理		CHKD 校对 NCH 2020/04/10
		SCALE 比例 1 : 1	UNIT 单位 mm	DR. 制图 ZPD 2020/04/10
DIMENSIONS		TOLERANCE		TITLE 名称 AD16-22 Buzzer
0.00 TO 18.00mm		±0.43mm		
18.01 TO 30.00mm		±0.52mm		
30.01 TO 50.00mm		±0.62mm		
50.01 TO 80.00mm		±0.74mm		
DWG NO. 图号 AD16-22 蜂鸣器		SHEET 张 1 / 1		SIZE 图纸 <b>A4</b>
FILE NAME 档案名称 AD16-22 蜂鸣器.DWG		REV. 更改 1		