

Unipolar flexible cables



RoHS
Conformity

Applications:
Unipolar flexible cable for electronics.

Characteristics:
 Conductor: O.F.C. red copper
 C130 PVC
 Insulation: C131 PVC HT 105°
 Sheath colours: White, Brown, Green, Yellow, Grey, Pink, Blue, Red, Black, Violet

Conductor Resistance	Max rated Voltage	Operative Temperature
$\Omega/\text{Km} \pm 5\%$	AC - V	°C
90	49	-15 / +70
60	49	-15 / +90

tasker® Code	Cond. number	Nominal section mm ²	Nominal section AWG	Cond. Format. mm.	External Cable Diameter mm.	Reel or Spool (* pag. II)		
						mt.	Type	Kg.
C130	1	1 x 0,22	24	7x0,20	1,2 PVC	200	B	0,7
C131		1 x 0,35	22	11x0,20	1,4 PVC HT 105°	200	B	1,0

Production on demand

RoHS
Conformity

Unipolar cable with Stiff Wire 6/10



Applications:
Unipolar cable with stiff wire 6/10 in tinned copper for electronics.

Characteristics:
 Conductor: O.F.C. tinned copper
 Insulation: PVC
 Sheath colours: Black, White, Red, Green, Blue, Yellow

Conductor Resistance	Max rated Voltage	Operative Temperature
$\Omega/\text{Km} \pm 5\%$	AC - V	°C
70	49	-15 / +70

tasker® Code	Cond. number	Nominal section mm ²	Nominal section AWG	Cond. Format. mm.	External Cable Diameter mm.	Reel or Spool (* pag. II)		
						mt.	Type	Kg.
C133	1	1 x 0,28	23	1x0,60 (6/10)	1,2	200	B	0,9

RoHS
Conformity

Unipolar flexible cable



Applications:
Unipolar flexible cable for tester and measuring devices.
Conductor composed of n° 64 of Ø mm. 0,10 copper wires.

Characteristics:
 Conductor: O.F.C. tinned copper
 Cond. Insulation: PVC
 Sheath colours: Black, Red

Conductor Resistance	Max rated Voltage	Operative Temperature
$\Omega/\text{Km} \pm 5\%$	AC - V	°C
45	49	-15 / +70

tasker® Code	Cond. number	Nominal section mm ²	Nominal section AWG	Cond. Format. mm.	External Cable Diameter mm.	Reel or Spool (* pag. II)		
						mt.	Type	Kg.
C205	1	1 x 0,50	20	64x0,10	2,5	100	B	1,3