



**Applications:** Unipolar flexible cable with double sheath for tester and measuring devices. Cable with conductors composed of extremely thin elementary wires (n° 126 of Ø mm. 0,10) that are first bound up in beams and then stranded for a better transmission of the signals.

**Characteristics:**  
 Conductor: O.F.C. red copper  
 Cond. Insulation: PVC  
 Core colour: White  
 External sheath: PVC  
 Sheath colours: Black, Red



| tasker®<br>Code | Cond.<br>number | Nominal<br>section<br>mm <sup>2</sup> | Nominal<br>section<br>AWG | Cond. Format.<br>mm. | External<br>Cable<br>Diameter<br>mm. | Reel or Spool<br>(* pag. II) |      |     |
|-----------------|-----------------|---------------------------------------|---------------------------|----------------------|--------------------------------------|------------------------------|------|-----|
|                 |                 |                                       |                           |                      |                                      | mt.                          | Type | Kg. |
| C206            | 1               | 1 x 1,00                              | 17                        | 18x7x0,10            | 4,1                                  | 100                          | B    | 2,7 |

| Conductor<br>Resistance | Max rated<br>Voltage | Operative<br>Temperature |
|-------------------------|----------------------|--------------------------|
| Ω/Km ± 5%               | AC - V               | °C                       |
| 21                      | 49                   | -15 / +70                |

Notes: