

# K15-23n

## Power Stage Cable



### Construction

### Cross Section

Conductor	OFC	
Jacket material	PVC Flame Retardant	
Fire Rating	FT2	
Jacket color	Bright Red (RAL 3020) Bright Black (RAL 9005)	

### Electrical Properties

Max. Rated Voltage	AC / CA 49 V
Operating Temp. Range	-15°C +70°C

### Packaging

Packaging	100m Cardboard Reel (K15-234 & K15-235)
	50m Cardboard Reel (K15-236 & K15-237)
	30m Cardboard Reel (K15-238 & K15-239)
Cable Marking	K15-237 EMELEC VíasCom 1x12,00 mm <sup>2</sup> "SPECIAL CAR" SERIES (Different for each item)
Color Marking	Silver (RAL 9006)

Code	Cores x Nominal section mm <sup>2</sup>	Stranding mm	Jacket mm	Resistance Ω/km
K15-234	1 x 4.00	51 x 7 x 0.12	5.4	4.5
K15-235	1 x 6.00	76 x 7 x 0.12	6.2	3.0
K15-236	1 x 8.00	102 x 7 x 0.12	7.0	2.6
K15-237	1 x 12.00	22 x 7 x 7 x 0.12	9.0	1.5
K15-238	1 x 16.00	29 x 7 x 7 x 0.12	11.0	1.2
K15-239	1 x 25.00	45 x 7 x 7 x 0.12	13.0	0.8