



STYLE	28AWG 6C TELEPHONE CABLE	ESTABLISHED DATE: FEB22,2013
CONDUCTOR	SIZE	28AWG
	MATERIAL	OFC (Oxigen Free Copper)
	CONSTRUCTION	7/Φ0.12±0.008mm (S twist:11.47mm)
INSULATION	AVG. THICK.	0.29mm
	MIN.THICK.	0.21mm
	DIAMETER	Φ0.95+/-0.05mm
	MATERIAL	PP
	COLOR	6C (GREEN RAL 6018, BROWN RAL 8001, WHITE RAL 9010, RED RAL 3020, BLUE RAL 5012, YELLOW RAL 1016)
JACKETED	AVG.THICK.	0.60mm
	MIN.THICK.	0.49mm
	DIAMETER	2.6±0.10mm*6.9±0.15mm
	MATERIAL	80°C 65Pa UL-PVC(WITH RoHS)
	COLOR	Q18 106:IVORY (RAL1015) (HALF MATTE) Q18 106B:WHITE (RAL9010)(HALF MATTE) Q18 106N:BLACK (RAL9005)(HALF MATTE)
ELECTRIC FUNCTION	CONDUCTOR RESISTANCE	MAX: 237.25 OHM/KM,20°C
	INSU.RESISTANCE	MIN:10M OHM/KM, 20°C
	CAPACITANCE Cond./Cond.	60pF/m
	DIELECTRIC STRENGTH	AC1000V 60HZ/1MIN
	FIRE RATING	FT2
PACKING	LABEL	Q18 106, Q18 106B, Q18 106N
	M/SPOOL	100m
	SIZE SPOOL	170*75*120mm(paper)
	SPOOLS/CARTON	4
MARKING	NO	
Product diagram		Axial plane pictures