



STYLE	28AWG 8C TELEPHONE CABLE	ESTABLISHED DATE: FEB22,2013
CONDUCTOR	SIZE	28AWG
	MATERIAL	OFC (Oxygen Free Copper)
	CONSTRUCTION	7/Φ0.12±0.008mm (S twist:11.47mm)
INSULATION	AVG. THICK.	0.29mm
	MIN.THICK.	0.21mm
	DIAMETER	Φ0.95+/-0.05mm
	MATERIAL	PP
	COLOR	8C(GREEN RAL 6018, BROWN RAL 8001, WHITE RAL 9010, RED RAL 3020, BLUE RAL 5012, YELLOW RAL 1016, ORANGE RAL 2011, BLACK RAL 9005)
JACKETED	AVG.THICK.	0.60mm
	MIN.THICK.	0.49mm
	DIAMETER	2.6±0.10mm*8.8±0.15mm
	MATERIAL	80°C 65Pa UL-PVC (WITH RoHS)
	COLOR	Q18 108:IVORY (RAL1015) (HALF MATTE) Q18 108B:WHITE (RAL9010)(HALF MATTE) Q18 108N:BLACK (RAL9005)(HALF MATTE)
ELECTRIC FUNCTION	CONDUCTOR RESISTANCE	MAX: 237.25 OHM/KM,20°C
	INSU.RESISTANCE	MIN:10M OHM/KM, 20°C
	CAPACITANCE COND./COND.	60pF/m
	DIELECTRIC STRENGTH	AC1000V 60HZ/1MIN
	FIRE RATING	FT2
PACKING	LABEL	Q18 108, Q18 108B, Q18 108N
	M/SPOOL	100m
	SIZE SPOOL	170*75*150mm(paper)
	SPOOLS/CARTON	4
MARKING	NO	
Product diagram		Axial plane pictures
		