

Caution!

- ▶ Never remove the screen holding the capsule, as this may damage the microphone!
- ▶ Never drop the mic, as this may cause severe damage!



Pre-announcement chime when microphone is switched on
LED lighted ring around the microphone when "on air"
Microphone and chime volume adjustable on backside
Gooseneck for convenient positioning

Microphone type:	Condenser
Output connections:	6.3mm Jack, XLR (3-pin)
Frequency Response :	20Hz - 22 KHz
Sensitivity:	-54±3dB(0dB=1V/Pa at 1kHz)
Load Impedance:	≥500Ω
Equivalent Noise Level:	11 dBA
Voltage:	100-240VAC 50/60Hz (12V Adapter)
Sampling Rate:	44.1Bit/192Kz



This product is subject to the European Waste Electrical and Elec-tronic Equipment Directive (WEEE) in its currently valid version. Do not dispose of your old device with your normal household waste. Dispose of this product through an approved waste disposal firm or through your local waste facility. Comply with the rules and regulations that apply in your country. If in doubt, consult your local waste disposal facility.



For the transport and protective packaging, environmentally friendly materials have been chosen that can be supplied to normal recycling. Ensure that plastic bags, packaging, etc. are properly disposed of. Do not just dispose of these materials with your normal house-hold waste, but make sure that they are collected for recycling. Please fol-low the notes and markings on the packaging.